



Miniature Quick-Connect Bodies, with Shutoff



Part No.

B-QM2-B-2PM

Part Description

Brass Miniature Quick Connect Body, 0.05 Cv, 1/8 in. Male NPT

Availability:

Specifications

General	
Air Inclusion	0.1 cm ³
Body Material	Brass
Body Valve Option	Standard Body Valve
Bulkhead	No Bulkhead
Cleaning Process	Standard Cleaning and Packaging (SC-10)
Configuration	Body
Connection 1 Size	1/8 in.
Connection 1 Type	Male NPT
eClass (4.1)	37110302
eClass (5.1.4)	37110302
eClass (6.0)	37-02-05-90
eClass (6.1)	37-02-05-00
Flow Coefficient	0.05 - If coupled with a DESO stem, 0.06 - If coupled with a SESO stem
Lubricant	Dow Corning 111
O-Ring	Buna N
Plating	Brite-Dip on Brass
Pressure Rating Coupled at Max Temp	100 PSIG @ 250 °F /6.8 BAR @ 121 °C
Pressure Rating Coupled at Room Temp	2000 PSIG @ 70 °F /137 BAR @ 21 °C
Pressure Rating UnCoupled at Room Temp	100 PSIG @ 70 °F /6.8 BAR @ 21 °C
Pressure/Temp_ Rating (Coupling and Uncoupling)	100 PSIG @ 70 °F /6.8 BAR @ 21 °C
Series	Miniature Quick-Connect
Size	1/8 in.
Spillage	0.1 cm ³
Testing	0.1 cm ³
UNSPSC (10.0)	27121701
UNSPSC (11.0501)	27121701
UNSPSC (13.0601)	27121701
UNSPSC (15.1)	27121701
UNSPSC (4.03)	31163101



FUELCELL
Store

UNSPSC (SWG01)

31163101

! The complete catalog contents must be reviewed to ensure that the system designer and user make a safe product selection. When selecting products, the total system design must be considered to ensure safe, trouble-free performance. Function, material compatibility, adequate ratings, proper installation, operation, and maintenance are the responsibilities of the system designer and user.

⚠ Caution: Do not mix or interchange valve components with those of other manufacturers.