



## Miniature Quick-Connect Stems, with Shutoff

IMAGE NOT  
AVAILABLE

**Part No.**

B-QM2-D-200

**Part Description**

Brass Miniature Quick Connect Stem with Valve, 0.05 Cv, 1/8 in. Swagelok Tube Fitting

**Availability:**

## Specifications

General	
Body Material	Brass
Bulkhead	No Bulkhead
Cleaning Process	Standard Cleaning and Packaging (SC-10)
Configuration	DESO Stem
Connection 1 Size	1/8 in.
Connection 1 Type	Swagelok® Tube Fitting
eClass (4.1)	37110302
eClass (5.1.4)	37110302
eClass (6.0)	37-02-05-90
eClass (6.1)	37-02-05-00
Flow Coefficient	0.05 - If coupled with a standard or reverse flow body
Lubricant	Dow Corning 111
O-Ring	Buna N
Pressure Rating Coupled at Max Temp	100 PSIG @ 250 °F /6.8 BAR @ 121 °C
Pressure Rating Coupled at Room Temp	2000 PSIG @ 70 °F /137 BAR @ 21 °C
Pressure Rating UnCoupled at Room Temp	100 PSIG @ 70 °F /6.8 BAR @ 21 °C
Pressure/Temp_ Rating (Coupling and Uncoupling)	100 PSIG @ 70 °F /6.8 BAR @ 21 °C
Series	Miniature Quick-Connect
Size	1/8 in.
Spring	Standard Spring
UNSPSC (10.0)	27121701
UNSPSC (11.0501)	27121701
UNSPSC (13.0601)	27121701
UNSPSC (15.1)	27121701
UNSPSC (4.03)	31163101
UNSPSC (SWG01)	31163101



# FUELCELL

Store

**!** The complete catalog contents must be reviewed to ensure that the system designer and user make a safe product selection. When selecting products, the total system design must be considered to ensure safe, trouble-free performance. Function, material compatibility, adequate ratings, proper installation, operation, and maintenance are the responsibilities of the system designer and user.

**⚠** Caution: Do not mix or interchange valve components with those of other manufacturers.